



REVISED AND ACTIVE - 2026-Q1

ADDRESS: Physical and Postal

The Uptown Theatre
1350 Third St.
Napa, California 94559

PHONE: 707.259.0123

FAX: 707.259.0333

WEBSITE: www.uptowntheatrenapa.com

TECHLINK: www.uptowntheatrenapa.com/technical-info

UPTOWN THEATRE NAPA PRODUCTION TEAM

UPTOWN THEATRE GENERAL MANAGER:

ERICA SIMPSON

Office: 707.259.0123 - ext. 2

Cell: 925.683.9933

erica@uptowntheatrenapa.com

UPTOWN THEATRE PRODUCTION MANAGER:

JOHN BREGLIA

Cell: 916.524.7914

john@uptowntheatrenapa.com

UPTOWN THEATRE SYSTEMS ENGINEER:

www.uptowntheatrenapa.com/technical-info

UPTOWN THEATRE LD & HEAD ELECTRICS:

EDDY HANSEN

Cell: 562.619.4210

elviso69eh@yahoo.com

www.uptowntheatrenapa.com/technical-info



REVISED AND ACTIVE - 2026-Q1

UPTOWN THEATRE LOGISTICS

1. LOAD-IN:

- FROM FRANKLIN ST
- STREET LEVEL - 12' RAMP UP TO UPSTAGE RIGHT WING.
- HEIGHT OF DOCK TO STREET LEVEL: - 3'-0"

2. TOUR BUS PARKING:

- (2X) STANDARD COACH TYPE BUSES
- (2X) SPOTS LOCATED EAST (THEATRE) SIDE OF FRANKLIN ST
- (3X) SPOTS LOCATED EAST SIDE OF RANDOLPH ST ALL BY PERMIT ONLY

3. TRUCK & SEMI PARKING:

- (1X) CONVENTIONAL EXTENDED SLEEPER TRACTOR W/ 53' TRAILER
- (1X) SPOTS LOCATED NORTH EAST (THEATRE) CORNER OF FRANKLIN ST @ SECOND ST.
- (3X) SPOTS LOCATED EAST SIDE OF RANDOLPH ST @ THIRD ST. ALL BY PERMIT ONLY

4. SHORE POWER:

- (2X) 60AMP SECURED BOXES W/ SIDEWALK CABLE TROUGH
- LOCATED EAST (THEATRE) SIDE OF FRANKLIN ST

UPTOWN THEATRE PRODUCTION LOCATIONS

- | | |
|------------------------------------|---|
| <u>1. FOH AUDIO POSITION:</u> | - CENTER OF HOUSE (FLOOR LEVEL) |
| <u>2. FOH LIGHTING POSITION:</u> | - CENTER OF HOUSE (FLOOR LEVEL) |
| <u>3. FOH DIMENSIONS:</u> | - 10' X 10' |
| <u>4. FOH POSITION TO DSC:</u> | - 45'-0" |
| <u>5. MONITOR POSITION:</u> | - UPSTAGE LEFT WING |
| <u>6. SPOT BOOTHS:</u> | - 2X LOCATED REAR OF THEATRE IN UPPER LOFT AREA |
| <u>7. SPOTS TO DSC:</u> | - 110'-0" |
| <u>8. PRODUCTION OFFICES:</u> | - UPSTAIRS OFF STAGE LEFT |
| <u>9. GREEN ROOMS:</u> | - 2X |
| - LARGE GREEN ROOM | - UPSTAIRS OFF UPSTAGE LEFT |
| - SMALL GREEN ROOM | - STREET LEVEL OFF UPSTAGE LEFT - HANDICAP ACCESSABLE |
| <u>10. KITCHEN & CATERING:</u> | - IN THE COURTYARD AT STREET LEVEL OFF UPSTAGE LEFT |

UPTOWN THEATRE STAGE DIMENSIONS

1. STAGE LOAD-IN DOOR: 3'-7½" WIDE X 9'-11" TALL
2. UPSTAGE WALL TO DOWNSTAGE EDGE: 23'-5"
3. INSIDE OF PROSCENIUM STAGE RIGHT TO STAGE LEFT: 35'-10"
4. OFF STAGE RIGHT TO OFF STAGE LEFT: (DOWNSTAGE OF THE PROSCENIUM: 37'-11")
5. OFFSTAGE WING STAGE RIGHT SIZE: 8' WIDE X 24' LONG
6. OFFSTAGE WING STAGE LEFT SIZE: 8' WIDE X 24' LONG
7. HEIGHT OF STAGE AT DOWNSTAGE EDGE: 3'-6"
8. DISTANCE FROM DOWNSTAGE EDGE TO FOH: 45'-0"



REVISED AND ACTIVE - 2026-Q1

UPTOWN THEATRE AC POWER SPECIFICATIONS

UPTOWN THEATRE LIGHTING & ELECTRICS POWER SYSTEMS:

PRO POWER CORP

- 400-AMP 3-Phase service
- dedicated and isolated
- HOUSE LIGHTING rig ONLY.
- located SR LOFT

PRO POWER CORP

- 200-AMP 3-Phase disconnect
- dedicated and isolated
- ARTIST AUXILIARY lighting ONLY.
- located SR LOFT

PRO POWER CORP ISO-20

- (2x) - 20-AMP "non-technical" circuits
- located at FOH lighting position

APPLIED ELECTRONICS MCDT-12

APPLIED ELECTRONICS MCC-12

- 12 channel dual twist chain hoist control system
- 12 channel handheld remote controller

UPTOWN THEATRE AUDIO POWER SYSTEMS:

PRO POWER CORP ISO-1K

- 1k-AMP isolation transformer

PRO POWER CORP

- 400-AMP 3-Phase service
- camlock tie-in with 25' feeder.
- HOUSE AUDIO power ONLY
- located SR LOFT

PRO POWER CORP

- 200-AMP 3-Phase service
- MONITOR + STAGE power ONLY
- located at USL wall.
- camlock tie-in with 5' feeder.

PRO POWER CORP DRM-200

- (2x) - 200-AMP rack mount disto's
- FOH + HOUSE AUDIO located SR LOFT
- MONITOR + STAGE AUDIO located USL

PRO POWER CORP ISO-60

- (2x) - 20-AMP "TECHNICAL" circuits
- located at FOH AUDIO position



REVISED AND ACTIVE - 2026-Q1

UPTOWN THEATRE LIGHTING RIG SPECIFICATIONS

UPTOWN THEATRE FOH LIGHTING CONSOLE:

AVOLITES PEARL 2010 - 240 Intelligent Fixtures + 240 Dimmer Control Channels

UPTOWN THEATRE DIMMER SYSTEMS:

LEPRECON 48C - 48x channel dimmer

UPTOWN THEATRE WIRELESS DMX SYSTEMS:

CITY THEATRICAL SHoW BABY - (3x) MULTIVERSE SHoW BABY
- 6-universe 2.4GHz wireless DMX transceivers

UPTOWN THEATRE TRUSS SYSTEMS:

DOWNSTAGE TRUSS:

- 40 foot box truss
- centered - 30' from DSC edge.
- trim height of 24'4"
- (2x) CM LODESTAR 1-ton motors

UPSTAGE TRUSS:

- 32 foot box truss
- located onstage, upstage of the proscenium.
- trim height of 18' (with black duvetyne truss border)
- (2x) CM LODESTAR 1-ton motors

US CROSSOVER TRUSS:

- 32 foot box truss
- located onstage, upstage of the US LIGHTING TRUSS.
- trim height of 18' (with black duvetyne drape on traveler)
- (3x) CM LODESTAR 1-ton motors

UPTOWN THEATRE FIXTURES and other LIGHTING SYSTEMS:

LEVITON P-64 - (40x) PAR 64 medium beam 1000 watt fixtures
- (30x) on Downstage Truss
- (10x) on Upstage Truss

ETC SOURCE 4 LEKO - (6x) ellipsoidal fixtures for 6 specials
- all top mounted on Downstage Truss

ADJ MEGA PROFILE- P64 - (18x) PAR 64 LED fixtures
- (12x) mounted on Upstage Truss
- (6x) available for ground use

LYCIAN 1275 SUPERSTAR 1.2 - (2x) 1200W follow spots
- located projection booth - rear of house LEFT and RIGHT

LEE GELS - Assorted - (12x) Colors

SAFE-T SYSTEMS SH-3 - (2x) Level III safety harness.

SAFE-T SYSTEMS - span sets, shackles, carabineers, static rope

The Uptown Theatre is a fully seated venue.



REVISED AND ACTIVE - 2026-Q1

UPTOWN THEATRE AUDIO SYSTEMS SPECIFICATIONS

UPTOWN THEATRE FOH AUDIO SYSTEMS:

<u>AVID VENUE PROFILE</u>	- 24x8 digital control surface
<u>AVID D-SHOW FOH RACK</u>	- 3x mix engines with redundant power supplies - located at FOH
<u>AVID D-SHOW STAGE RACK</u>	- 48x8 I/O - located at STAGE LEFT
<u>AVID D-SHOW 3.0x</u>	- firmware
<u>AVID VENUE TOUR PACK 3</u>	- plug-in package
<u>AVID ECx</u>	- CAT5 ethernet option card
<u>AVID FWx</u>	- FIREWIRE 1394 option card w/ <u>VENUE LINK</u> capability
<u>APC SMART-1000-RM2</u>	- UPS (uninterrupted power supply)
<u>HP HD1750</u>	- 17" LCD screen
<u>LOGITEK</u>	- USB keyboard with trackball

UPTOWN THEATRE FOH AUDIO SNAKE SYSTEMS:

All snakes terminate at MONITOR-WORLD STAGE LEFT

<u>HI-TECH AUDIO DIGI-SNAKE</u>	- 150' - 4-way dual redundant BNC
<u>WHIRLWIND CAT-5-SNAKE</u>	- 150' - 3-way redundant CAT-5 run
<u>WHIRLWIND ANALOG SNAKE</u>	- 150' - 48*8 Copper

UPTOWN THEATRE FOH AUDIO PROCESSING SYSTEMS:

<u>MEYER SOUND GALILEO 616</u>	- loudspeaker management system
<u>MEYER SOUND COMPASS</u>	- Galileo remote control software on <u>LENOVO Tablet PC</u>
<u>D-LINK DIR-655 GIGABYTE</u>	- wireless router for Galileo remote access

UPTOWN THEATRE FOH AUDIO LOUDSPEAKER SYSTEMS:

<u>MEYER SOUND MICA</u>	- (16x) compact high-power "Curvilinear" array loudspeaker - flown (8x) per side - trim height - 20' - deck clearance - 10'-10" - (4x) <u>CM LODESTAR</u> 1-ton motors @ (2X) per MICA array
<u>MEYER SOUND 700-HP</u>	- (4x) ultrahigh-power subwoofer - matrix or aux derived "sub" - located underneath the DSC edge of the stage
<u>MEYER SOUND UPA-2P</u>	- (2x) compact narrow coverage loudspeaker - Galileo derived "outfill" - located off midstage right and left
<u>MEYER SOUND M1D</u>	- (5x) ultra-compact "Curvilinear" array loudspeaker - matrix or aux derived "frontfill" - located along the DS edge of the stage



REVISED AND ACTIVE - 2026-Q1

UPTOWN THEATRE AUDIO SYSTEM SPECIFICATIONS - CON'T

UPTOWN THEATRE MONITOR AUDIO SYSTEMS:

<u>AVID SC48</u>	- 48x32(24+8) digital console system
	- dual redundant power supplies
<u>AVID D-SHOW 3.0x</u>	- firmware
<u>AVID TOUR PACK 2</u>	- plug-in package
<u>HP HD1750</u>	- 17" LCD screen
<u>APC SMART-1000-RM2</u>	- UPS (uninterrupted power supply)
<u>LOGITEK</u>	- USB keyboard with trackball
<u>AVID FWx</u>	- FIREWIRE 1394 Card w/ <u>VENUE LINK</u> capability
<u>AVID ECx and UltraVNC</u>	- remote desktop software on <u>LENOVO Tablet PC</u>
<u>D-LINK DIR-655 GIGABYTE</u>	- wireless router for remote desktop access

UPTOWN THEATRE MONITOR AUDIO LOUDSPEAKER SYSTEMS:

<u>MEYER SOUND MJF-212A</u>	- (5X) - high-power stage monitor
	- dual 12" - tri-amped
<u>MEYER SOUND UM-1P</u>	- (5x) - narrow coverage stage monitor
	- single 12" - bi-amped
<u>MEYER SOUND USW-1P</u> - (1x)	- compact subwoofer (drum sub)
	- dual 15" - bi-amped

UPTOWN THEATRE MICROPHONE PACKAGE:

<u>SHURE Beta 52A</u>	- (1x) - dynamic microphone
<u>SHURE Beta 91</u>	- (1x) - condenser boundary layer microphone
<u>SHURE SM81</u>	- (4x) - cardioid condenser microphone
<u>SHURE SM58</u>	- (8x) - dynamic microphone
<u>SHURE SM57</u>	- (8x) - dynamic microphone
<u>SHURE SM58S</u>	- (2x) - dynamic microphone w/ switch
<u>SENNHEISER MD421 II</u>	- (4x) - dynamic microphone
<u>SENNHEISER e906</u>	- (4x) - super cardioid dynamic microphone
<u>SENNHEISER e904</u>	- (4x) - dynamic microphone w/ integral drum mounts
<u>COUNTRYMAN TYPE 85</u>	- (6x) - active DI
<u>RADIAL JDI</u>	- (2x) - passive DI w/ Jensen transformer

UPTOWN THEATRE MICROPHONE STANDS PACKAGE:

<u>ATLAS DMS-10CE</u>	- (8x) - round base mic stand	- short
<u>ATLAS MS-12CE</u>	- (8x) - round base mic stand	- standard
<u>ATLAS MS-36RC</u>	- (2x) - HD round base mic stand	- HD w/ boom arm
<u>K&M STMS-10B</u>	- (12x) - HD tripod mic stand	- HD w/ boom arm
<u>K&M TBA-24</u>	- (12x) - telescoping boom arm	- short



REVISED AND ACTIVE - 2026-Q1

UPTOWN THEATRE AUDIO SYSTEM SPECIFICATIONS - CON'T

UPTOWN THEATRE STAGE SNAKE SYSTEMS:

<u>WHIRLWIND CS-W4-ISO-56</u>	- 56 channel transformer isolated splitter system
<u>WHIRLWIND CS-W4</u>	- (2x) - 10' - 56 channel W4 whip (MAIN + ISO OUTS)
<u>WHIRLWIND CS-FO-XLR</u>	- (2x) - 15' - 6 channel XLR fan-out
<u>WHIRLWIND CS-SB</u>	- (1x) - 50' - 16x4 sub-snake w/ stage box
<u>WHIRLWIND CS-SB</u>	- (2x) - 50' - 10x2 sub-snake w/ stage box
<u>WHIRLWIND CS-RSB</u>	- (2x) - 50' - 0x6 RETURN ONLY sub snake w/ stage box

UPTOWN THEATRE MICROPHONE CABLE PACKAGE:

<u>WHIRLWIND MK4</u>	- (4x) - 100' - XLR mic cable
<u>WHIRLWIND MK4</u>	- (6x) - 50' - XLR mic cable
<u>WHIRLWIND MK4</u>	- (20x) - 25' - XLR mic cable
<u>WHIRLWIND MK4</u>	- (16x) - 20' - XLR mic cable
<u>WHIRLWIND MK4</u>	- (28x) - 15' - XLR mic cable
<u>WHIRLWIND MK4</u>	- (12x) - 10' - XLR mic cable
<u>WHIRLWIND MK4</u>	- (12x) - 3' - XLR mic cable

UPTOWN THEATRE COMMUNICATION PACKAGE:

<u>RTS SAP-612</u>	- 6x12 Matrix - w/ RTS PS-15 - dual rackmount power supply unit
<u>RTS CIA-1000</u>	- (2x) amber beacon - (1)@ FOH + (1)@ SL - MONITOR AUDIO
<u>RTS BP-325</u>	- (8x) belt pack - (1x)@ FOH AUDIO + (1x)@ FOH LD + (1x)@ MONITOR AUDIO - (1x)@ SL - STAGE MANAGER + (1x)@ SR - ASSIST SM - (2x)@ SPOT BOOTH L+R
<u>BEYER DYNAMIC DT 109</u>	- (6x) dual muff headsets
<u>BEYER DYNAMIC DT 108</u>	- (6x) single muff headsets



REVISED AND ACTIVE - 2026-Q1

UPTOWN THEATRE STAGING SPECIFICATIONS

- QUIK-STAGE QS4X8PQRBLK**
- SIX(6)x 8ft*4ft*4in aluminum decks
w/ black non-skid quad-ripple polyvinyl deck surface
 - SIX(6)x legs per deck
 - THIRTY-SIX(36)x 1ft aluminum legs
 - TWELVE(12)x 1.5ft aluminum legs
 - THIRTY-SIX(36)x 2ft aluminum legs (only for 24*8ft riser build)

UPTOWN THEATRE VIDEO RIG SPECIFICATIONS

PROJECTOR, PLAYBACK, SCREEN and other VIDEO SYSTEMS:

- EIKI LC-UXT3**
- 1080i HD 3-CHIP LCD video projector
 - 10kW lumens w/ 4-bulb dynamic focus
 - 1.8 – 2.3 Short Throw High Angle Lens
 - IR wireless and hardwired remote
 - DELICATE PRODUCTIONS custom mount system
 - projector hung from DS truss for front projection

- OPPO BDP-93**
- Blu-Ray Player
 - 3D compatible w/ advanced up scaling
 - 5.1 THX capable

- SCREENWORKS FASTFOLD**
- 21' x 12' front projection screen

- MONOPRICE HDMI-AP**
- dual redundant active HDMI snake
 - HD / 4k capable
 - 250' run - FOH to the projector

- DELICATE HD-5**
- 5-wire BNC trunk
 - VGA - HD capable
 - 250' run - FOH to the projector

- BARCO G62 - W14**
- **AVAILABLE BY SPECIAL REQUEST ONLY**
 - **THIS ITEM WILL INCURE A \$2700 RENTAL CHARGE**
 - 4K UHD NEXTGEN LED video projector
 - 18kW lumens w/ dynamic focus
 - Medium and Long Throw Lens options
 - IR wireless and hardwired remote
 - projector mounted onto 10ft vertical truss system
 - projector located at FOH for front projection